

S 28 X

SPECIFICATIONS

	U.S.	Metric
Vertical Reach	90' 11"	27.7 m
Horizontal Reach	77' 9"	23.6 m
Below Grade Reach w/ Tip Hose	57' 1"	18 m
Pipeline Diameter	5 in	125 mm
Boom Type/ Sections	Combination Roll & Fold with Z Boom/ 4	
Boom Rotation	370 degrees	
Unfolding Height	19' 2"	5.8 m
Outrigger Type- Front	Hydraulic Telescoping & Jacking	
Outrigger Type- Rear	Manual Extension, Hydraulic Jacking	
Outrigger Soil Pressure w/o Dunnage (front/rear)	281/265 psi	19.4/18.3 bar
Outrigger Soil Pressure w/ Dunnage (front/rear)	70/66 psi	4.8/4.6 bar
Outrigger Width, Front	19' 7"	5.9 m
Outrigger Width, Rear	11' 10"	3.6 m
Outrigger Length	21' 7"	6.6 m

PUMP SPECIFICATIONS

	U.S.	Metric
Theor. Concrete Output	208 cu yds/h	159 cu m/h
Max. Pressure on Concrete	1007 psi	70 bar
Max. Strokes Per Minute (rod/piston)	32	
Max. Aggregate size	2.5 in	63.5 mm
Material Cylinder Diameter	9 in	230 mm
Material Cylinder Stroke	79 in	2006.6 mm
Differential Cylinder Diameter	5.1 in	130 mm
Maximum Oil Flow	132.1 gal/min	500 l/min
Hydraulic Circuitry Type	MPS	
Valve Type	M Rock	

*Pump specifications are for standard units. Other units are available. Specifications are subject to change without prior notice.

